



NOTE:

1. THE U-VALUE PACKAGE CONSISTS OF ALL FEATURES LISTED FOR THE SL500 CONCEALED AND SURFACE APPLIED, NARROW/MEDIUM/WIDE STILE, SINGLE SLIDE, AND BIPART CONFIGURATIONS OF BOTH FIXED SIDELITE AND FULL BREAK OUT CONFIGURATIONS.
SEE THE APPROPRIATE TECH MANUAL DRAWINGS FOR STANDARD FEATURES AND OPTIONS AND FOR DIMENSIONAL INFORMATION.
THE U-VALUE OPTION INCLUDES THE BESAM ECODOOR SEAL OPTION.
2. THE U-VALUE DOOR ACCEPTS 1"(25.4mm) INSULATED GLASS IN THE SIDELITES AND IN THE ACTIVE LEAVES.
3. INFILTRATION RATING REQUIRES FIELD VERIFICATION OF ALL SEALS AND SEAL ALIGNMENT. ECODOOR SEAL SYSTEM EXCEEDS ASHRAE 90.1 2010 REQUIREMENT FOR INFILTRATION. (0.93 CUFT/MIN/SQFT 0.28M³/M²/MIN),
4. OPTIONAL FULL THRESHOLD SHOWN, SEE SL500 DOOR TECH MANUAL DRAWING(S) FOR FLOOR TRACK & RECESSED TRACK OPTIONS.
5. GLASS SELECTION MUST MEET THE SPECIFICATION OUTLINED ON THE PRODUCT NFRC "U" RATING CERTIFICATION. NFRC TEST DOCUMENTATION AVAILABLE ON REQUEST.
6. 1" INSULATED GLASS SPECIFICATION FOR U-VALUE RATING OF 0.64BTU/HR*FT²*F (EXCEEDS ASHRAE 90.1-2010 FOR ZONES 1 THRU 8.), REFER TO TEST DOCUMENTATION.

DWG. NO.		1011375	
DRN BY	mdv	DATE	2/27/13
CHK BY		DATE	
REV	4.0	DATE	1/21/15

ASSA ABLOY

SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE
SOLE PROPERTY OF ASSA ABLBY ENTRANCE SOLUTIONS. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE
WRITTEN PERMISSION OF ASSA ABLBY ENTRANCE SOLUTIONS
IS PROHIBITED.