

	OVERALL	ROUGH	CLEAR	DOOR	BREAKOUT
	FRAME WIDTH	OPENING	OPENING	WIDTH	WIDTH
	(A)	(B)	(C)	(D)	(E)
	108"	108 1/2"	46 1/8"	53 3/4"	98.00"
	[2743.2]	[2755.9]	[1171.6]	[1365.3]	[2490.0]
	B - 1/2"	A + 1/2"	A/2 - 7 7/8"	A/2 - 1/4"	A - 10"
	B - [12.7]	A + [12.7]	A/2 - [200]	A/2 - [6.35]	A - [254.0]
ΗT	104" [2641.6]	104 1/4" [2648.0]	94" [2387.6]		
	B - 1/4" B - [6.35]	A + 1/4" A + [6.35]	A - 10" A - [254.0]		

GLASS FORMULA: OFW /2 - 5 5/8[142.9] X OFH -20 1/2 [520.70]

NOTES:

STANDARD PACKAGE CONSISTS OF:

- · STANDARD FINISH:
- CLASS 1, .018MM, CLEAR- AA-M12C22A41
- CLASS 1, .018MM, DARK BRONZE- AA-M12C22A44
- · AUTOMATIC OPERATOR
- · NARROW STILE RAILS
- · THRESHOLD
- · 3-POINT LOCK WITH LOCK INDICATOR
- 9/16" GLASS STOPS AND BLOCKS
- 1/4" HS .090" DUPONT SENTRYGLAS PLUS® 1/4" HS DRY GLAZED
- MOTION/PRESENCE SENSORS
- · 5-POSITION KNOB SWITCH
- · BALL CATCH
- DUAL CONCEALED SWEEPS IN SX & SO PANELS
 4" BOTTOM RAILS

OPTIONS AVAILABLE:

- · SPECIAL FINISHES
- · PANIC EXIT DEVICE
- · 1" IG O.A. LAMINATED GLASS
- \mathscr{H}_6 " HS .090" DUPONT SENTRYGLAS PLUS® \mathscr{H}_6 " HS \mathscr{Y}_6 " AIR GAP \mathscr{H}_6 " FT 7" /10" BOTTOM RAILS
- THRESHOLD LEAD-UP, SEE SHEET AA-30 FOR DETAILS
- TRUE DIVIDED MUNTINS
- · FALSE MUNTINS
- SEE SHEET OS-10 FOR ALL OTHER OPTIONS AND OPTION DETAILS

FOR MAXIMUM CURRENT DRAW, SEE PRODUCT SPECIFICATION, INSTALLATION INSTRUCTIONS, OR THE UL LABEL ON THE EQUIPMENT.

TEST PROTOCOLS: ASTM F842-17 GRADE 25

REFER TO RELEVANT [LOCAL, STATE, NATIONAL, OR AHJ] BUILDING CODE FOR MIN DOOR HEIGHT & MIN/MAX WIDTH ALLOWABLE FOR EGRESS REQUIREMENT IN CONJUNCTION WITH TABLE.

DWG NC	^{D.} 10212	204				
DRN BY	SJF	DATE 7/8/2020	CHK BY	DATE	^{REV.} 3.0	DATE 1/21/22
_						
	$\mathbf{}$					
A	33	A ABL	UY			