## **GLASS OPTIONS FOR ASSA ABLOY FRAME**

## \* Tempered glass not available for ASSA ABLOY Frame Telescopic

	DESCRIPTION	U-value	GLASS CODE
	6 mm laminated glass, with single foil	5,7	GL6
*	6 mm tempered glass	5,7	GT6
	8 mm laminated glass, with single foil	5,6	GL8
	8 mm laminated glass, with double foils	5,6	GL8.2
*	8 mm tempered glass	5,7	GT8
	10 mm laminated glass, with single foil	5,6	GL10
	10 mm tempered glass	5,6	GT10
	22 mm insulated glass, with single foil and air	2,9	GI22
	22 mm insulated glass, with single foil, TopN and air	1,8	GI22.1
	22 mm insulated glass, with double foils, TopN and air	2,0	GI22.2
	22 mm insulated glass, with single foil, TopN and argon	1,4	GI22.1AR
	22 mm insulated glass, with double foils, TopN and argon	1,7	GI22.2AR
	22 mm insulated glass, with single foil, TopN and krypton	1,0	GI22.1KR
	22 mm insulated glass, with double foils, TopN and krypton	1,2	GI22.2KR
	40 mm insulated glass, with single foil and air	2,7	GI40
	40 mm insulated glass, with double foils, TopN and air	1,4	GI40.2
	40 mm insulated glass, with double foils, TopN and argon	1,1	GI40.2AR
	40 mm insulated glass, with double foils, lplus and Krypton	1,0	GI40.2KR

ASSA ABLOY Entrance Systems AB, 2020 echnical data subject to change without notic

Customer:	Ref:
Door id:	Date:
Project No:	) Sign:

