High speed door ASSA ABLOY HS9010PL



Experience a safer and more open world



Large sized high speed door for inside applications

The main features of the ASSA ABLOY HS9010PL are:

- Large-sized, max. 11000 x 6500 mm
- Heavy-duty operations
- Inside usage
- Galvanised steel construction
- Unique direct door drive system
- Opening speed up to 1,4 m/s

The unique dual barrel power drive system eliminates the need for weighted bottom bars or tension systems by actively driving the door curtain. Exceptional reliability and smooth operation is ensured by a frequency converter driven motor for a soft start and stop.

The reliable and versatile control unit ensures precise door set up and diagnostics and is enclosed in a robust steel control box. A customer friendly clear display gives a wide range of information like an easy to read cycle counter.

Break-away and Automatic Reset system

ASSA ABLOY high speed doors are equipped with a break-away and automatic reset system. The curtain reintroduces itself after a crash to reduce downtime and maintenance.

Completely safe

- Features that make our doors completely safe.
- The soft bottom profile has no rigid parts, it gives way should an obstruction be in the line of closing.
- If the door is hit, the fabric curtain absorbs the impact and releases itself from its side guides without causing damage or being damaged itself.

Windows

To increase the admission of daylight or to improve the visibility, the door curtain can be equipped with pre-defined windows.

Technical Data

Min size (W x H)	2000 x 2000 mm
Max size (W x H) ¹	11000 x 6500 mm
Operating speed ²	opening: up to 1,4 m/s closing: up to 0,6 m/s
Wind load resistance, EN 12424	class 1 (300 N/m²)
Water penetration, EN 12425	class 1 (30 N/m ²)
Air permeability, EN 12426	class 1 (24 m³/m²/h at 50 Pa)
Thermal transmittance	6,02 W/(m ² K)
Performance Test	750.000 cycles
1) Max $61m^2$. Other sizes available on request 2) Depending on door size	

Dimensional specifications



Windows



Options access and automation



© ASSA ABLOY | PL.HS9010PL/en-ORG/2022-03 Technical data subject to change without notice.