

SPECIFICATION	OPTIONS		WINDOWS:	
DOOR TYPE: NASSAU9000	Automatic closing		Panel Options:	
VARIANT: F G M P	Reversing a closing door		90W 90M 90G 90P 90P	
Standard Lift SL	Pull Rope		Fillings for 90W windows	
High Lift HL	Photocells		SA - SA = Double 2.5mm Standard Acrylic (SAN)	
High Lift with bracket fixed Springs HLKF	Remote control		SA - PA = 2.5mm Standard Acrylic (SAN) on outside + 3mm Pearl Acrylic on inside	
Vertical Lift VL	Magnetic Loop		HG - SA = 3mm Tempered glass on outside + 2.5mm Standard Acrylic (SAN) on Inside	
Vertical Lift with bracket fixed Springs HLKF	Radar		POLY - SA = 3mm Polycarbonate on outside + 2.5mm Standard Acrylic (SAN) on Inside	
High Lift with bracket fixed Springs HLKF	Traffic lights		Fillings for 90G \$ 90M windows	
Low Height Lift (Garage door) LHTL	Warning lights		3-15-3 = Double 2.5mm Standard Acrylic (SAN)	
OPERATION:	Reduced opening		3-15-3C1 = Double 2.5mm Standard Acrylic (SAN) with	
CONTROL PANEL:	Aırlock		scratch-resistant KASI® external finish.	
TS959 (Deadman)	PASSDOOR: (Viewed from inside)		3-15-3C2 = Double 2.5mm Standard Acrylic (SAN) with scratch-resistant KASI® internal \$ external fi	ınısh.
TS97 (Impulse up & Down)	Left hand hung	Right hand hung	3-15-3PA = 2.5mm Standard Acrylic (SAN) on outside + 3mm Pearl Acrylic on inside	
MATERIAL:	On left In Center	On right	3-15-3HG = 4mm Tempered glass on outside + 2.5MM Standard Acrylic (SAN) on inside	
Aluminium	LOCKING:		3-15-3POLY = 3mm Polycarbonate on outside + 2.5MM Standard Acrylic (SAN) on inside	
FINISHES:	Lockbolt Cylinde	er Lock	4PL = Single 4mm Acrylic (PMMA)	
Standard Ral 9002 - off white	PASS DOOR THRESHOLD:		3PL-PA = Single 3mm Pearl Acrylic	
Other (specify Ral / BS colour)	Standard (180mm) Low Level (23mm)		4HG = Single 4mm Tempered Glass	
EXTERNAL (Standard polyester options)				
**Ral 3000 - Red Ral 9002 - Off White				
**Ral 5010 - Blue Ral 9005 - Black			GLAM = Gmm Laminated Glass (3mm + foil + 3mm)	
**Ral 6005 - Moss Green Ral 9006 - White Alu.			S = Single 1.5mm Stucco Aluminium SI = Double 1.5mm Stucco Aluminium with	
Ral 7016 - Anthracite Grey **Ral 9007 - Grey Alu.			I 8mm EPS insulation	
**Ral 702 - Black Grey Ral 90 0 - Pure White			A = Single 1.5mm Smooth Anodised Aluminium	
**Ral 8017 - Chocolate Brown			Al = Double 1.5mm Smooth Anodised Aluminium with EPS Insulation	
**BS 8B25 - Merlin Grey			APSIO = 3mm powder coated aluminium with I 0mm square holes	
**BS IOAO5 - Goosewing Grey			Fillings for 90P windows	
Other (specify Ral / BS colour)			3-15-3PC = Double 3mm external \$ internal polycarbonate	
** Denotes that the colour is only available in Aluminium material	© COPYRIGHT AAES Dimensions in mm. TOLERANCES +/- 3mm (DO NOT SCALE - if in doubt ask)		3-15-SANC2 = Double 3mm Standard Acrylic (SAN) with scratch-resistant KASI® external finish.	
TITLE.	CLIENT:	DRAWING STATUS	DRAWN BY:	
ASSAABLOY NASSAU 90 OPTION LIST	DO SECTIONAL DOOR	RELIMINARY	CHECKED BY:	
ASSA ABLOY Entrance Systems Ltd Industrial Door and Docking Solutions	F	OR APPROVAL	DATE:	
rchill Way .35A Business Park .Chapeltown .Sheffield .UK .535 2PY Tel: +44 (0) 4 257 4330 Fax: +44 (0) 4 257 4399		ONSTRUCTION	DRAWING No.	REV
Steel Timbe	r Masonry Other A	BUILT REV. BY	DATE COMMENT NAS9000-OPTIONS	