
ASSA ABLOY

ASSA ABLOY Entrance Systems 1900 Airport Road Monroe, NC 28110 Phone: 1-866-237-2687 specdesk.na.besam@assaabloy.com ASSA ABLOY SL500 SA-SL

SURFACE APPLIED, FULL BREAKOUT NARROW STILE SINGLE SLIDE DOOR SYSTEM



NOTE: THE STANDARD PACKAGE CONSISTS OF:

THE AUTOMATIC OPERATOR & WEATHERSTRIP, FRAMES, DOORS WITH VERTICAL WEATHERSTRIP, EMERGENCY BREAKAWAY

& 1-POINT LOCK. OPTIONAL 5 POSITION SWITCHES (DIGITAL (3 OR 5) OR KEY (5)), (OFF-EXIT ONLY-AUTO-REDUCED OPENING-HOLD OPEN OR OFF, AUTO, HOLD OPEN), MOTION/PRESENCE SENSORS.

STANDARD FINISH: CLEAR- AA-M12C22A41, CLASS 1, .018 MM. DARK BRONZE- AA-M12C22A44, CLASS 1, .018 MM

SPECIAL FINISHES ARE AVAILABLE.

THIS PACKAGE WILL ACCEPT UP TO 1" (25.4) INSULATED GLASS.

NOTE DRAWING IS DIMENSIONED IN BOTH ENGLISH AND METRIC REF. AS FOLLOWS 1" (25.4) ALL METRIC SIZES ARE MILLIMETERS.

* FOR MAXIMUM CURRENT DRAW PER OPERATOR, SEE PRODUCT SPECIFICATION, INSTALLATION INSTRUCTIONS, OR THE UL LABEL ON THE EQUIPMENT.

REFER TO RELEVANT (LOCAL, STATE, NATIONAL OR AHJ) BUILDING CODE FOR MIN DOOR HEIGHT & MIN/MAX WIDTH ALLOWABLE FOR EGRESS REQUIREMENT IN CONJUNCTION WITH TABLE BELOW.

MASONRY OPENING WIDTH C	ACTIVE LEAF WIDTH D	DOOR OPENING A	OVERALL FRAME HEIGHT	ROUGH OPENING HEIGHT	OVERALL FRAME WIDTH B
36 ″	38 5/8 "	32 3/8 "	91 "	84"	78 1/4 "
(914.4)	(981.1)	(822.3)	(2311.4)	(2134)	(1987.6)
42 "	44 5/8 "	38 3/8 "	91 "	84"	90 1/4 "
(1066.8)	(1133.5)	(974.7)	(2311.4)	(2134)	(2292.4)
48 "	50 5/8 "	44 3/8 ″	91 "	84"	102 1/4 "
(1219.2)	(1285.9)	(1127.1)	(2311.4)	(2134)	(2597.2)
50 7/8 *	53 1/2"	47 1/4"	91 "	84"	108 "
(1292.2)	(1358.9)	(1200.2)	(2311.4)	(2134)	(2743.2)
KEY	C+2 5/8"	C-3 5/8"	ROH+7"	0FH-7"	2C+6 1/4"
	C+(66.7)"	C-(92.1)	ROH+(177.8)	0FH-(177.8)	2C+(158.8)"

OFW NOTE: CONSULT FACTORY FOR EXTENDED HEADERS.

STD. GLASS SIZE KEY*	WIDTH	C-2 1/4" C-(57.2)	*FOR SIDELITE, MINUS 1/8" FROM GLASS
	HEIGHT	(OFH)-15 7/8" (OFH)-(403.2)	FORMULA SHOWN

* NARROW STILE RAILS w/ 1/4" GUTTER, NO MUTTINS BASED ON MASONRY OPENING

