

ASSA ABLOY Entrance Systems
1900 Airport Road
Monroe, NC 28110
Phone: 1-866-237-2687
specdesk.na.entrance@assaabloy.com

SW200i IS DESIGNED FOR HIGH PERFORMANCE, HEAVY
USAGE PEDESTRIAN APPLICATIONS THAT COMPLY WITH
ANSI A156.10. THE OPERATOR CAN ALSO BE ADJUSTED
FOR LOWER MANUAL PUSH FORCES TO COMPLY WITH
ANSI 156.19 AND FIRE DOOR REGULATIONS.

NOTE: DRAWING IS DIMENSIONED IN BOTH ENGLISH
AND METRIC, REF. AS FOLLOWS: 1: (25.4).
ALL METRIC SIZES ARE IN MILLIMETERS.

NOTE: *

NET CLEAR (EGRESS MIN 32' (813)) DOOR

ENCROACHMENT OF 4" INTO NET CLEAR BY
PANIC HARDWARE IS PERMITTED ABOVE 34".

* GUIDE RAILS (SHOWN) ARE REQUIRED ON THE
SWINGPATH SIDE OF POWER OPERATED PEDESTRIAN
DOORS (ANSI 156.10) BUT NOT ON LOW ENERGY
POWER OPERATED DOORS (ANSI 156.19).

| | | | | | | | | | | | | | | | | | | | | | |
|---|--|-----|------|--|----------|--|--------|--|----|------|---|----------|--|------|--|-----|------|--|---------|--|--|
| DWG NO. 1015876 | | | | | | | | | | | | | | | | | | | | | |
| DRN BY | | MHW | DATE | | 10/20/16 | | CHK BY | | SS | DATE | | 10/20/16 | | REV. | | 2.0 | DATE | | 1/17/18 | | |
| <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> | | | | | | | | | | | | | | | | | | | | | |
| ASSA ABLOY | | | | | | | | | | | <div></div> <div></div> <div></div> <div></div> | | | | | | | | | | |